



Sage
OILVAC
WIND



Sage Oil Vac

Manufacturers of on-site maintenance equipment



GEAR OIL EXCHANGE SYSTEM

VERSATILE • DEPENDABLE • PRACTICAL

TOLL FREE **1-800-015580** • www.oilvacsystems.com.au
Telephone: 0894340999, Email: sales@oilvacsystems.com.au
Oil Vac of Australia, 20 Ambitious Link, Bibra Lake. WA 6163

OILVAC
of Australia 

The Gear Oil Exchange System can deliver ISO 320 viscosity grade gear oil at a rate of 4-6 gallons (15-22 liters) per minute. *

The Gear Oil Exchange System can vacuum gear oil directly from the tower gearbox at a rate of 2-4 gallons (8-15 liters) per minute. *

Fresh oil may be vacuumed into the new oil tanks at rates of 10-20 gallons (38-76 liters) per minute*

*Actual delivery and suction times depend on factors affecting viscosity, such as oil temperature and ambient temperature.

Trailer Options



Enclosed Trailer



Open Trailer



Connect directly to the gearbox to decrease spills and drips. Eliminate heavy lifting injuries and dangerous spills.



Filter new oil overnight to achieve recommended ISO cleanliness levels. Fresh oil may pass through filtration system 3-4 times for optimum results.



Dual hoses are mounted on hand re-wind hose reels and are lifted up tower together. Standard hose length is 330 feet (100 m) on all models. Longer hose length is available.



On-board heating system heats fresh oil for improved flow.



Vacuum in fresh oil directly from oil tote or barrel to reduce spills.



Secondary Containment Pan holds a minimum of 430 gallons of fluid.

Gear Oil Exchange System



(shown on open trailer)



(shown on open trailer)

Tanks gallons / (liters)	29250	29253	29393	29394
Used Oil	250 / (946)	250 / (946)	390 / (1476)	390 / (1476)
Fresh Oil	250 / (946)	250 / (946)	390 / (1476)	390 / (1476)
Flush Fluid	n/a	120 / (454)	120 / (454)	120 / (454)
Rinse Fluid	n/a	n/a	n/a	120 / (454)
Length feet / (m)	13' 8" / (4.16)	16' 4" / (4.98)	16' 4" / (4.98)	20' 6" / (6.25)
Width feet / (m)	6' 6" / (1.98)	6' 6" / (1.98)	6' 6" / (1.98)	6' 6" / (1.98)
Empty Weight lbs / (kg)	3540 / (1605)	4470 / (2027)	5330 / (2417)	7945 / (3603)
Maximum Weight lbs / (kg)	7140 / (3238)	8934 / (4052)	11900 / (5398)	15300 / (6939)

Note: Measurements are for skid-mounted equipment. Open or enclosed trailers add additional length and weight depending on options. Enclosed trailers are insulated and equipped with lights and recommended for northern climates and/or winter maintenance.

Equipment shown is for illustrative purposes and may display optional accessories or components. Sage Oil Vac reserves the right to make changes in engineering, design or specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. © 2011 Sage Oil Vac Inc. All Rights Reserved.